## COPY OF PAPERS ORIGINALLY FILED

ereby certify that this document is being deposited with the United States Postal Service as

first class mail in an envelope addressed to Assistant Commissioner For Patents, Washington,

DC 20231 on 4/18/02

Date of signature

4/18/02

IN THE UNITED STATES PATENT AND TRADEMARKS OFFICE

APPLICANT: ORIS NELSON

**SERIAL NUMBER: 09/776876** 

FILED:2/6/01

**GROUP ART UNIT:2859** 

DOCKET NUMBER 1 20011

**EXAMINER: PRUCHNIC, STANLEY** 

FOR: DIAMOND DETECTING APPARATUS AND METHOD

Commissioner of Patents and Trademarks

Washington, DC20231

**AMENDMENT** 

SIR,

In response to the office action of 4/1/02, please amend the application as follows: IN THE SPECIFICATION:

Replace the paragraph beginning on line 13 of page 3 with the following amended paragraph:

Referring now to the method of operation, the steps of the method are depicted in Fig. 2 as follows;

21 The mounting of the stone is held in one hand. 22 The housing is held in the other hand. 23 The probe is applied to the surface of the stone to be tested. 24 The apparatus is turned on. 25 After a preset warm up period of about 10 seconds, 26 the thermal conductivity is measured and the results displayed. After a 0.5 second delay, 27 the electrical conductivity is measured and the results are displayed. When both the thermal and electrical conductivity displays are positive, the stone is thereby determined to be a true diamond. Furthermore, if the thermal conductivity test is positive and the electrical conductivity test is negative, it indicates that the stone is moissanite. Such simulated stones as cubic zirconia have much lower thermal conductivity than diamond.

**REMARKS** 

S

1